

\*

1-1

© Behr Hella Service GmbH, Schwäbisch Hall

01. Oktober 2005

## **Opel** Vectra C / Signum

## **Changed filling levels**

The filling level of the refrigerant and/or compressor oil has changed with some of the above-mentioned models. The currently valid filling levels are as follows:

| Engine  | Model year | Refriger<br>ant level<br>R134a | OE<br>compresso<br>r oil type | Hella<br>compress<br>or oil type | Compress<br>or oil filling<br>level |
|---|------------|--------------------------------|-------------------------------|----------------------------------|-------------------------------------|
| Z16XE,<br>Z18XE,<br>Z32SE,<br>Z20NET,<br>Z22SE,<br>Z22YH,<br>Y20DTH,<br>Y20DTH,<br>Y22DTR | Up to 2005 | 730 g                          | 90509933                      | PAO 68<br>or PAG<br>ISO 46       | 120 ml                              |
| Z19DT,<br>Z19DTH  | Up to 2005 | 730 g                          | 90509933                      | PAO 68<br>or PAG<br>ISO 46       | 135 ml                              |
| Y30DT   | Up to 2005 | 680 g                          | 90509933                      | PAO 68<br>or PAG<br>ISO 46       | 120 ml                              |

Since technical/design-related changes by the vehicle manufacturer are always possible, the filling levels can change again. Which means these specifications are not guaranteed.

